
ELECTROMAGNETIC BRAKE

MBC024-24-002


Mach Motion Products


REV	DESCRIPTION	DATE	APPROVE
A	RELEASE	24/09/09	ZZF




NOTE:
1. VOLTAGE: 24VDC
2. STATIC TORQUE: 1.5Nm Min.
3. RATED CURRENT: 0.56A
4. POWER: 13.3W
5. RESISTENCE: 39 Ohms
6. START VOLTAGE: 22VDC MAX.
7. HI-POT: 500VAC/1S, 2mA
8. PERMANENT MAGNET BRAKE
   BROWN CONNECT +, THE BRAKE IS RELEASED;
   BROWN CONNECT −, THE BRAKE IS LOCKED.


MOTOR INTERFACE:







* CUSTOM LABEL



NOTE: THIS DRAWING HAS BEEN CREATED BY AUTOCAD. MANUAL REVISIONS ARE NOT ALLOWED.

MATERIAL			TOLERANCE UNLESS OTHERWISE SPECIFIED ISO 2768-1 MEDIUM		
DRAWN XXX	CHECKED	APPROVED – DATE	FILENAME	DATE xx/xx/xx	SCALE N/A
		BRAKE			
		MBC024-24-002			SHEET 1/1

This drawing and the information disclosed herein are proprietary data of Mach Motion Products, and is to be immediately returned upon request. Reproduction of this drawing or the information contained herein is prohibited wihtout the expressed written approval of Mach Motion Products.